

# GH6000H



# PORTABLE POWER

# Technical

Model GH 6000H – 'Hire Spec'

Type Portable
Speed 3000 RPM
Phase/Voltage 1/240
Frequency 50 Hz
Max Output @ 0.8pf
Noise Level (dBA @ 72

**7m) Frame** Extra Large roll frame

### **Engine**

ManufacturerHondaEngine ModelGX390TypeO.H.V.

Starting Recoil & Electric start
Fuel Unleaded Petrol

**Run Time** 2.6 hr @ 100%, 3.8hrs @60%

Tank Capacity6.1 LHP 3000 rpm cont8.0 HPCubic Capacity389 Cm3Oil Capacity1.1 L

#### **Alternator**

Alternator Brand Meccalte
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

#### **Outlets**

Outlet IP66 Rated 10amp + 15amp switched with Earth Leakage Circuit Breakers & RCD

## **Dimensions & Weight**

 Length
 85 Cm

 Width
 57 Cm

 Height
 60 Cm

 Weight
 56 Kg

#### **Options**

Wheel kits Two wheel or four wheel Frames Extra large Roll Frames

**Alternators** Oversized, Single or Three Phase

**Long Range Tank** 15 Litre Capacity



