

PRODUCT SPECIFICATIONS FOR 815



ENGINE - TIER 4 FINAL/EU STAGE V

Engine Model	Cat® C7.1: configured for two emissions options
Net Power (SAE J1349:2011)	186 kW
Net Power (ISO 9249:2007)	186 kW
Emissions	Meets U.S. EPA Tier 4 Final/EU Stage V emission standards
Rated Speed	2200 r/min
Gross Power (SAE J1995:2014)	212 kW
Engine Power (ISO 14396:2002)	205 kW
Peak Torque - 1,400 rpm	1223 N·m
Torque Rise	52%
Bore	105 mm
Stroke	135 mm
Displacement	7.01 l
High Idle Speed	2270 r/min
Low Idle Speed	800 r/min
Maximum Altitude without Derating	3000 m

Note

Net power advertised is the power available at the engine flywheel when the engine is equipped with a fan, air cleaner, clean emissions module and alternator.

ENGINE - BRAZIL MAR-1 AND CHINA NONROAD STAGE III, EQUIVALENT TO TIER 3/EU STAGE IIIA

Engine Model	Cat® C7.1: configured for two emissions options
Net Power (SAE J1349:2011)	186 kW
Emissions	Brazil MAR-1 and China Nonroad Stage III, equivalent to U.S. EPA Tier 3/EU Stage IIIA
Rated Speed	2200 r/min
Gross Power (SAE J1995:2014)	213 kW
Engine Power (ISO 14396:2002)	205 kW
Peak Torque - 1,400 rpm	1016 N·m
Torque Rise	26%
Bore	105 mm
Stroke	135 mm
Displacement	135 mm
High Idle Speed	2270 r/min
Low Idle Speed	800 r/min
Maximum Altitude without Derating	3000 m

Note

Net power advertised is the power available at the engine flywheel when the engine is equipped with a fan, air cleaner, clean emissions module and alternator.

OPERATING SPECIFICATIONS - TIER 4 FINAL/EU STAGE V

Operating Weight	22522 kg
------------------	----------

TRANSMISSION

Transmission Type	Cat Planetary Power Shift
-------------------	---------------------------

Travel Speeds - Forward - First	6.3 km/h
---------------------------------	----------

Travel Speeds - Forward - Second	10.8 km/h
----------------------------------	-----------

Travel Speeds - Forward - Third	18.2 km/h
---------------------------------	-----------

Travel Speeds - Reverse - First	7.2 km/h
---------------------------------	----------

Travel Speeds - Reverse - Second	12.4 km/h
----------------------------------	-----------

Travel Speeds - Reverse - Third	18.4 km/h
---------------------------------	-----------

HYDRAULIC SYSTEM - LIFT/TILT

Lift/Tilt System - Circuit	Pilot operated LS valve with EH
----------------------------	---------------------------------

Lift/Tilt System	Variable displacement piston
------------------	------------------------------

Maximum Flow at 2,200 rpm	89 l/min
---------------------------	----------

Relief Valve Setting - Lift/Tilt	22000 kPa
----------------------------------	-----------

Pilot System	Open center, fixed displacement gear
--------------	--------------------------------------

Pilot Relief Valve Setting	21000 kPa
----------------------------	-----------

HYDRAULIC SYSTEM - STEERING

Steering System - Circuit	Pilot, Load Sensing
Steering System - Pump	Piston – Variable Displacement
Maximum Flow at 2,200 rpm	147 l/min
Relief Valve Setting - Steering	27600 kPa
Total Steering Angle	84
Steering Cycle Times - High Idle	3 s
Steering Cycle Times - Low Idle	8.2 s

SERVICE REFILL CAPACITIES

Fuel Tank	500 l
Diesel Exhaust Fluid Tank*	16 l
Cooling Systems - Tier 4 Final/EU Stage V	81 l
Cooling System - Tier 3/Stage IIIA Equivalent	73 l
Engine Crankcase	20 l
Transmission	56 l
Differential - Final Drives - Front	65 l
Differential - Final Drives - Rear	65 l

Hydraulic Tank Only 75 l

Note All non-road Tier 4 Final and Stage V diesel engines are required to use: – Ultra Low Sulfur Diesel (ULSD) fuels containing 15 ppm for EPA and 10 ppm for EU (mg/kg) sulfur or less. Biodiesel blends up to B20 are acceptable when blended with 15 ppm for EPA and 10 ppm for EU (mg/kg) sulfur or less ULSD and when the biodiesel feedstock meets ASTM D7467 specifications. – Cat DEO-ULS™ or oils that meet the Cat ECF-3, API CJ-4, and ACEA E9 specifications are required. – Diesel Exhaust Fluid (DEF) that meets all requirements defined in ISO 22241-1.

DIMENSIONS (APPROXIMATE)

Height - Top of Beacon	3933 mm
Height - Top of Cab Roof	3650 mm
Height - Top of Exhaust Pipe	3344 mm
Height - Top of Hood	2616 mm
Height to Top of Radiator Guard	2405 mm
Ground Clearance to Hitch	365 mm
Ground Clearance to Transmission Guard	375 mm
Ground Clearance to Bottom of Bumper	665 mm
Centerline of Rear Axle to Bumper	1990 mm
Hitch to Centerline of Front Axle	1675 mm
Wheel Base	3350 mm
Width over Platform	3140 mm
Height to Top of GPS Antenna	3701 mm
Overall Machine Length with Straight Blade	7157 mm

Overall Machine Length with EU Suppression

7598 mm

AXLES

Front Planetary – Fixed

Rear Planetary – Oscillating

Oscillation Angle ± 10

BRAKING SYSTEM

Service Brakes Single Disc Wet (Enclosed) 2 WHL

Parking Brake Drum and Shoe, Spring Applied, Hydraulic Released

SOUND PERFORMANCE - TIER 4 FINAL/EU STAGE V - STANDARD

Operator Sound Level (ISO 6396) 70 dB(A)

Machine Sound Level (ISO 6395) 111 dB(A)

Note (1) The operator sound pressure level was measured according to the test procedures and conditions specified in ISO 6396:2008. The measurement was conducted at the maximum engine cooling fan speed.

Note (2) The operator sound pressure level uncertainty is ± 2 dB(A)

Note (3) Hearing protection may be needed when the machine is operated with a cab that is not properly maintained or when the doors or windows are open for extended periods or in a noisy environment.

Note (4) The operator sound pressure level was measured according to the test procedures and conditions specified in ISO 6396:2008. The measurement was conducted at the maximum engine cooling fan speed.

SOUND PERFORMANCE - TIER 4 FINAL/EU STAGE V - SUPPRESSION

Operator Sound Level (ISO 6396) 70 dB(A)

Machine Sound Level (ISO 6395) 109 dB(A)

Note (1) The operator sound pressure level was measured according to the test procedures and conditions specified in ISO 6396:2008. The measurement was conducted at the maximum engine cooling fan speed.

Note (2) The operator sound pressure level uncertainty is ± 2 dB(A)

Note (3) Hearing protection may be needed when the machine is operated with a cab that is not properly maintained or when the doors or windows are open for extended periods or in a noisy environment.

Note (4) The machine sound power level was measured according to the test procedures and conditions specified in ISO 6395:2008. The measurement was conducted at the maximum engine cooling fan speed.

SOUND PERFORMANCE - BRAZIL MAR-1 AND CHINA NONROAD STAGE III, EQUIVALENT TO TIER 3/EU STAGE IIIA - STANDARD

Operator Sound Level (ISO 6396) 70 dB(A)

Machine Sound Level (ISO 6395) 112 dB(A)

Note (1) The operator sound pressure level was measured according to the test procedures and conditions specified in ISO 6396:2008. The measurement was conducted at the maximum engine cooling fan speed.

Note (2) The operator sound pressure level uncertainty is ± 2 dB(A)

Note (3) Hearing protection may be needed when the machine is operated with a cab that is not properly maintained or when the doors or windows are open for extended periods or in a noisy environment.

Note (4) The machine sound power level was measured according to the test procedures and conditions specified in ISO 6395:2008. The measurement was conducted at the maximum engine cooling fan speed.

SOUND PERFORMANCE - BRAZIL MAR-1 AND CHINA NONROAD STAGE III, EQUIVALENT TO TIER 3/EU STAGE IIIA - SUPPRESSION

Operator Sound Level (ISO 6396)	70 dB(A)
--	----------

Machine Sound Level (ISO 6395)	110 dB(A)
---------------------------------------	-----------

Note (1) The operator sound pressure level was measured according to the test procedures and conditions specified in ISO 6396:2008. The measurement was conducted at the maximum engine cooling fan speed.

Note (2) The operator sound pressure level uncertainty is ± 2 dB(A)

Note (3) Hearing protection may be needed when the machine is operated with a cab that is not properly maintained or when the doors or windows are open for extended periods or in a noisy environment.

Note (4) The machine sound power level was measured according to the test procedures and conditions specified in ISO 6395:2008. The measurement was conducted at the maximum engine cooling fan speed.

SOUND PERFORMANCE - TIER 4 FINAL/EU STAGE V - SUPPRESSION EU

Machine Sound Level (ISO 6393)	107 dB(A)
---------------------------------------	-----------

Note (1) The machine sound power level was measured according to the test procedures and conditions specified in ISO 6393:2008. The measurement was conducted at the rated engine cooling fan speed.

WHEELS

Weight	4409 kg
---------------	---------

Outside Diameter	1412 mm
-------------------------	---------

Drum Diameter	1029 mm
----------------------	---------

Drum Width	991 mm
-------------------	--------

Tips per Row	12
Tips per Wheel	60
Replaceable	Weld On
Width - Over Drums	3243 mm
Width Between Drums	1261 mm
Tip Height	192 mm

BLADES

Capacity	2.06 m ³
Overall Width	3761 mm
Height	860 mm
Digging Depth	222 mm
Ground Clearance	802 mm
Maximum Tilt	346 mm
Turning Radius - Outside Corner of Blade	6437 mm
Turning Radius - Inside Face of Pusharm	2520 mm
Weight	800 kg
Total Operating Weight	22522 kg

815 STANDARD EQUIPMENT

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

POWER TRAIN

Advanced Productivity Electronic Control System (APECS)
Air to air aftercooler
Brakes, full hydraulic, enclosed, wet multiple disc service brakes
Cat clean emission module (Tier 4 Final/Stage IV only)
Electro-hydraulic parking brake
Electronic Clutch Pressure Control (ECPC)
Engine, Cat C7.1 (configured for two emissions options): – Tier 4 Final/Stage V – Tier 3/Stage IIIA equivalent
Engine driven cooling fan – suction
Fuel priming pump (electric)
Fuel to air cooler
Ground level engine shutoff
Muffler (under hood) (Tier 3/Stage IIIA equivalent only)
Radiator, unit core
Starting aid (ether)
Throttle lock
Torque converter
Transmission, planetary, with 3F/3R speed range control

ELECTRICAL

Alarm, back-up
Alternator, 150 amp
Batteries, maintenance-free
Electrical system, 24V
Ground level lockable master disconnect switch
Lights, directional (rear)
Light, warning switched (LED strobe)
Lighting system, (front and rear)
Starter, electric
Starting receptacle for emergency start

OPERATOR ENVIRONMENT

12V power port for mobile phone or laptop connection
AccuGrade™ mapping (ready)
Air conditioner
Cab, sound-suppressed pressurized
Cab door, sliding window (LH)
Cat Compaction Control (ready)
Cat Detect: Object Detection (ready)
Coat and hard hat hooks
Finger tip shifting controls
Flip-up armrest
Heater and defroster
Horn, electric
Hydraulic controls – seat mounted
Implement hydraulic lockout

Instrumentation, gauges: – DEF fluid level (Tier 4 Final/Stage V only) – Engine coolant temperature – Fuel level – Hydraulic oil temperature – Speedometer/tachometer – Torque converter temperature
Instrumentation, warning indicators: – Action alert system, three categories – Brake oil pressure – Electrical system, low voltage – Engine failure malfunction alert and action lamp – Parking brake status
Light, (dome) cab
Lunch box and beverage holders
Mirror, internal (panoramic)
Mirrors, rearview (externally mounted)
Radio ready for entertainment: – Antenna – Speakers – Converter (12V, 10-15 amp)
Seat, Cat Premium Plus (leather)
Seat belt with minder, retractable, 76 mm (3 in) wide
STIC control system with lockout
Sun visor, front
Tinted glass
Transmission gear (indicator)
Vital Information Management System (VIMS): – Graphical information display – External data port – Customizable operator profiles – Event indicator light on rear grill
Wet-arm wipers/washers (front and rear): – Intermittent wipers (front and rear)

TIRES, RIMS AND WHEELS

Wheels, tamping foot

GUARDS

Cleaner bars with teeth
Guards, crankcase and power train
Guard, driveshaft

FLUIDS

Antifreeze, premixed 50% concentration extended life (-34° C/-29° F)

OTHER STANDARD EQUIPMENT

DEF tank fill gauge
Doors, service access (locking)
Ecology drains for engine, radiator, transmission, hydraulic tank
Engine, crankcase, 500 hour interval with CJ-4 oil
Emergency platform egress
Fire suppression ready
Fuel tank, 500 L (132.1 gal)
Hitch, drawbar with pin
Hoses, Cat XT™
Hydraulic, engine, and transmission oil coolers
Oil change system, high speed
Oil sampling valves
Steering, load sensing
Total hydraulic filtration system
Vandalism protection caplocks

Venturi stack

STANDARD ATTACHMENTS – HYDRAULICS

Hydraulics: – Standard or EU and Canada

STANDARD ATTACHMENTS – OPERATOR ENVIRONMENT

Glass (window): – rubber-mounted glass

Precleaner (cab): – powered

Seat (cab): – heated and ventilated

Mirrors – cab: – Standard or heated

STANDARD ATTACHMENTS – POWER TRAIN

Axles: – Standard or non-spin rear

STANDARD ATTACHMENTS – SPECIAL ARRANGEMENTS

Engine Precleaners: – Turbine or dual stage

STANDARD ATTACHMENTS – ELECTRICAL

Lights: – Standard or LED

STANDARD ATTACHMENTS – FUEL SYSTEMS

Fuel tank: – Non-fast or fast fill

STANDARD ATTACHMENTS – TECHNOLOGY PRODUCTS

Product Link: – GSM, satellite

STANDARD ATTACHMENTS – CLEANER BARS

Cleaner bars: – Standard or abrasive

STANDARD ATTACHMENTS – BLADES

Blades: – Straight or tilt-straight

815 OPTIONAL EQUIPMENT

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

OPERATOR ENVIRONMENT

Camera, rear vision

Radio, AM/FM/AUX/USB/BLUETOOTH

Radio, CB (ready)

TECHNOLOGY PRODUCTS

Compaction control, basic

OTHER ATTACHMENTS

Sound suppression (required for Brazil)

FLUIDS

Antifreeze, -50° C (-58° F)

STARTING AIDS

Heater, engine coolant, 120V

Heater, engine coolant, 240V

MISCELLANEOUS

Film (ANSI) (Tier 4 Final/Stage V only)

EU certification (Tier 4 Final/Stage V only)

Plate - year of manufacture (Tier 3/Stage IIIA equivalent only)