

GH7000E



PORTABLE POWER

Technical

GH 7000E Model Type Portable Speed 3000 RPM Phase/Voltage 1/240 Frequency 50 Hz 7.0kW Max power kW **Continuous Output** 8.0kVA Noise Level (dBA @ 7m) 72

Frame Extra Large roll frame

Engine

ManufacturerHondaEngine ModelGX390TypeO.H.V.

Starting Recoil & Electric start
Fuel Unleaded Petrol

Run Time 2.6 hr @ 100%, 3.8hrs @60%

Tank Capacity6.1 LHP 3000 rpm cont8.0 HPCubic Capacity389 Cm3Oil Capacity1.1 L

Alternator

Alternator Brand Meccalte
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Outlets

Outlet 10amp + 15amp switched with thermal overload

Dimensions & Weight

 Length
 85 Cm

 Width
 57 Cm

 Height
 60 Cm

 Weight
 80 Kg

Options

Outlets Weather protected IP33 & Weatherproof IP66

Protection RCD/ELCB IP30 or IP66
Wheel kits Two wheel or four wheel
Frames Extra large Roll Frames

Alternators Oversized, Single or Three Phase

Long Range Tank 15 Litre Capacity

