



- 350W/VA UPS module designed to operate in extreme environments; providing maximum flexibility while ensuring critical loads remain protected and running during power outages and other power disturbances
- Unsurpassed flexibility with dual 120Vac and 24Vac outputs
- Wide range Automatic Voltage Regulation (AVR) lengthens battery life by providing protection without transferring to backup mode during voltage surge or sag
- Local and remote monitoring and control via USB port and Ethernet SNMP interface
- Temperature compensated battery charging protects batteries from overcharging at extreme temperatures, extending the life of the battery
- Independently programmable control and report dry contacts allow monitoring and controlling of key functions

FXM is a line of rugged UPS power modules used worldwide in the most demanding environments where clean backup power is needed. Designed to perform in the most extreme demanding environments, FXM units ensure equipment in security, communications, traffic, industrial environments, and many other critical applications remain safe and protected from power disturbances. Thanks to its powerful programmable battery charger, the FXM is capable of providing the runtime you need. All FXM models are available in 120Vac and 230Vac.

FXM 350 Rugged UPS Module

Consult your representative for P/N configurations

Electrical

| | |
|--------------------------|------------------------------------------------------------------------|
| > 120Vac Model | Battery string voltage: 48Vdc or 24Vdc |
| | Nominal voltage: 120Vac |
| | Frequency: 60/50Hz ±5% (auto-detection) |
| | Input: Voltage range (w/o transferring to battery mode): 88 to 152Vac |
| | Current: 5.3A |
| | • FXM350-24: 5.3A |
| | • FXM350-48: 5.7A |
| | Output: Pure sine wave |
| | Waveform: Dual 120Vac, 24Vac |
| | Nominal voltage: ±10% |
| | Voltage regulation: 350W/VA Total |
| | Power at 50°C: 260W/VA (max) |
| | • 24Vac: 260W/VA (max) |
| | • 120Vac: 350W/VA (max) |
| | Frequency: Output frequency = Input frequency |
| > 230Vac Model | Battery string voltage: 24Vdc |
| | Nominal voltage: 230Vac |
| | Frequency: 60/50Hz ±5% (auto-detection) |
| | Input: Voltage range (w/o transferring to battery mode): 151 to 282Vac |
| | Current: 2.7A |
| | Output: Pure sine wave |
| | Waveform: 230Vac, 24Vac |
| | Nominal voltage: ±10% |
| | Voltage regulation: 350W/VA Total |
| | Power at 50°C: 260W/VA (max) |
| | • 24Vac: 260W/VA (max) |
| | • 230Vac: 350W/VA (max) |
| | Frequency: Output frequency = Input frequency |

Mechanical

Mounting: 19" or 23" rack with the addition of ears for rack mounting

Dimensions: mm: 88.14H x 342W x 198D
 inches: 3.5H x 13.46W x 7.8D
 Weight: 8.62kg (19lbs)

Environmental

Operating temp range: -40 to 74°C (-40 to 165°F)
 Audible noise @ 25°C: <45dBA @ 1 meter (39in)

Performance

Typical output voltage THD: <3%
 Typical efficiency: >96%
 Typical transfer time: <5ms

Power Connector Options

| 120Vac Model | |
|--------------|----------------|
| Input | Terminal Block |
| Output | Terminal Block |
| 230Vac Model | |
| Standard | Terminal Block |
| Standard | Terminal Block |

Agency Compliance

Electrical safety: ULL1778, CSA C22.2 No. 107.3, EN60950-1, EN62040-1-2



EMC: FCC Part 15/B, EN55022, Class A, EN62040-2

*Derates above 50°C (122°F)
 **CE applies to 230Vac version only