CONVECTION STEAMER ECO COMBI-HECME4



TECHNICAL DATA

| Flow Pressure | 2-4 bar |
|-----------------------------------|----------------|
| Recommended water hardness | 3 - 4.5 °dH |
| Total loading Electro Standard | 6.0 kW 8.7 A |
| Noise levell | <70 dB(A) |

INDUSTRY KITCHENS

www.industrykitchens.com.au 1800 611 058

PRODUCT ADVANTAGES

- Uniform cooking process:
 - Oscillating fan
 - Separating grid between fan and cavity
 - With efficient ventilator
- Speed of the cooking process:
 - Efficient and fast steam production
 - Fast temperature transition due to an open grid
 - Rapid cool function
- Efficient automatic cleaning system:
 - Automatic, economic and fast
 - Programmes:
 - Short: 35 minutes
 - Medium: 43 minutes
 - Long: 51 minutes
 - Fast: 2 minutes water only
 - Rinsing: 20 minutes water

- Crosswise loading enables easy handling, a better view and more safety
- Basic touch display with practical and intuitive icons
- Fan Control: 6 speeds
- Water injection technology and rapid cooling of the cavity
- · Core Probe for accurate cooking
- SUPPLIED WATER TREATMENT SYSTEM MUST BE INSTALLED ON THE INCOMING WATER SUPPLY FEEDING THE COMBI OVEN

CONNECTIONS

| ① Fresh-water connection |
|--------------------------|
| ② Drain connection |
| ③ Power connection |
| ④ Chemical hose |
| ⑤ Equipotential |
| connection |
| © Ventilation |
| ⑦ Ventilation nozzle |

| 3/4" | |
|------------------|---|
| 1" | |
| 400 / 50 / 3N-PE | |
| 1500 mm | |
| M6 | |
| | |
| | |
| | _ |

DIMENSIONAL DRAWING

