

item #	
model #	
project #	
sis#	
aia #	



# HHT082E Hot holding trolley

### CONSTRUCTION FEATURES

- Tightness chamber with radiuses corners
- All-around rubber bumpers
- Total thermic insulation with rock or glass wood
- Long lasting front and door seals made up of food glade of high heat resistance
- Removable side racks to facilitate cleaning
- Static heating provided by low consumption wire heating element that coils up all the chamber
- Ergonomic and fully built-in door handle with magnetic closure
- Mounted on four 125 mm diameter castors, two of which with brake
- Ergonomic handle for pushing and guiding
- Easy access to facilitate maintenance and repair

### FUNCTIONAL FEATURES

- Electronic control of the temperature
- Operating temperature 30°-120°C
- Two adjustable humidity vents on the door
- Chamber with safety thermostat

#### STANDARD SUPPLY

• Removable GN 2/1 and GN 1/1 tray racks

## OPTIONS & ACCESSORIES

☐ Pass-through design




#### **TECHNICAL INSTALLATION DIAGRAM**


Electricity supply cable inlet



Adjustable vent for release of excess humidity



755 855



Overall dimensions (W x D x H) - mm

755 x 855 x 1010

Trays capacity

8 x GN 2/1 16 x GN 1/1

Tray max. height

8 x 65 (h)

GN 2/1 [mm]

3 x 150 (h)

2 x 200 (h) + 2 x 65 (h)

Tray max. height

16 x 65 (h)

GN 1/1 [mm]

6 x 150 (h)

4 x 200 (h) + 4 x 65 (h)

Power kW

1,5

Power supply

AC 230 V / 50 Hz



- A Display
- B ON/OFF switch
- C Temperature decrease key
- D Temperature increase key
- E START/STOP key

#### MODULINESRL