



| TECHNICAL DATA | | | | |
|-----------------------------|--|-------|-------|--------|
| EXTERNAL DIMENSIONS | | | | |
| width | 1490 mm | | | |
| depth | 885 mm | | | |
| height | 1970/2295mm (door open) | | | |
| WEIGHT(basic version) | 340 kg | | | |
| VOLTAGE | 400V 3N 50Hz | | | |
| POWER REQUIRED | 14800 W | | | |
| WATER HARDNESS | 2-8 °F | | | |
| INLET WATER PRESSURE | 200-400 kPa | | | |
| CROCKERY DIMENSIONS | | | | |
| size allowed | 820 mm | | | |
| RACK DIMENSIONS | | | | |
| 1350x725 mm | | | | |
| RACK EQUIPMENT | | | | |
| 1XC86/A - 1XC97/A - 1X93600 | | | | |
| WASHING CYCLES (min) | 1 (3) | 2 (6) | 3 (9) | 4 (12) |
| WATER SUPPLY 55°C | | | | |
| racks/h(*) ⁽¹⁾ | 20 | 10 | 6 | 5 |
| WATER SUPPLY 10°C | | | | |
| racks/h(*) ⁽¹⁾ | 10 | 10 | 6 | 5 |
| WATER CONSUMPTION / CYCLE | 8,6 L | | | |
| BOILER CAPACITY | 20 L | | | |
| BOILER HEATING ELEMENT | 9000 W | | | |
| RINSING TEMPERATURE (SET) | 85°C | | | |
| TANK CAPACITY | 148 L | | | |
| TANK HEATING ELEMENT | 9000 W | | | |
| TANK TEMPERATURE (SET) | 55°C | | | |
| WASHING PUMP POWER | 2900 W (950 L/min ^{***}) x 2 | | | |
| RINSING PUMP POWER | 250 W (150 L/min ^{***}) x 2 | | | |
| DRAIN PUMP (optional) | 190 W (120 L/min ^{***}) | | | |
| ACOUSTIC PRESSURE | 71,9 dB(A) | | | |

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.