



The pump is a light and compact high head submersible clean water automatic pressure system pump supplied wired and ready to install. The pump includes an electronic automatic restart pump control with dry run protection.

The pump is characterised by:

- Corrosion resistant pump components.
- Fully automatic operation.
- Shaft seal with sand protection boot.
- 240V single phase motor with in-built auto reset thermal overload.
- 15m of power cable.
- 2 year warranty.
- Flows to 95 l/m
- Heads to 46 m

Electrical data:

| | |
|---------------------|---------------------------|
| Rated voltage: | 240V |
| Mains frequency: | 50 Hz |
| Rated output: | 750W |
| Rated output: | 1100W |
| Current: | 4.8 amps |
| Motor duty: | Continuous |
| Motor type: | Asynchronous |
| Motor protection: | In-built thermal overload |
| Ingress protection: | IP 68 |
| Insulation class: | F |
| Power cable length: | 15 m H07RNF |
| Net weight: | 11.0 kg |
| Dimensions: | 480L x 150H x 150W (mm) |

Liquid:

Clean water temperature range: 2 – 35 °C

Materials:

| | |
|----------------|---|
| Pump body: | Noryl |
| Impellers (4): | Noryl with stainless steel wear ring |
| Diffusers (4): | Noryl with floating dry run resistant wear ring |
| Pump shaft: | SS416 |
| Shaft seal: | Nitrile |

Installation:

| | |
|------------------------------|-------|
| Maximum ambient temperature: | 40 °C |
| Maximum submergence: | 15m. |
| Pipe connections discharge: | 1" |

2 Year Dab Pump Warranty

