

Reinforced Storage

External reinforced data storage for DVR / MDVR



Features

- The saved data can be accessible or recoverable after car crash, fire, explosion, immersion, and etc.
- Refractory performance up to the standard of a flight black box (EUROCAEED-155:2009)
- Keep intact in a rapid cooling environment

Specification

Model No.	Reinforced Storage
Power Input	5V±5%
Power Consumption	< 0.5W
Interface	USB2.0
Medium	MLC
Writing Circulation	3000 times
Capacity	64GB
Refractory	1100°C / 2012°F for 15 minutes 950°C / 1742°F for 20 minutes 260°C / 500°F for 120 minutes
Immersion	100m deep water for 24 hours
Impact Force	100g 100ms
Static Extrusion Force	3000kg 5min
Pin Penetration	100kg 3m
Dimensions	129 x 62 x 91mm / 5.08" x 2.44" x 3.58"
Weight	2.1kg / 4.63lb

*All images presented in this document are for example only. Product models may vary in different countries. Please visit EverFocus regional Websites for detailed ordering information.

*Information contained in this document is subject to change without notice.

Find Out More At:

EverFocus Taiwan HQ:

TEL: +886 2 2698 2334

www.everfocus.com.tw

marketing@everfocus.com.tw

EverFocus USA - California:

TEL: +1 626 844 8888

www.everfocus.com

sales@everfocus.com

International Branch Offices:

Germany, China, Japan