

REVERSING ALARMS



160B



PART NO.	SOUND CYCLE	FREQUENCY	CURRENT DRAW @12v	OPERATING VOLTAGE	DIMENSIONS
160B-97	60-65 PM	1250-1300Hz	0.2 AMPS	12-80 VDC	102mm (L) 41mm (W) 70mm (H)
160B-102	60-65 PM	1250-1300Hz	0.25 AMPS	12-80 VDC	102mm (L) 41mm (W) 70mm (H)
160B-107	60-65 PM	1250-1300Hz	0.4 AMPS	12-80 VDC	102mm (L) 41mm (W) 70mm (H)
160B-112	60-65 PM	1250-1300Hz	0.5 AMPS	12-24 VDC	102mm (L) 41mm (W) 70mm (H)

170B



PART NO.	SOUND CYCLE	FREQUENCY	CURRENT DRAW @12v	OPERATING VOLTAGE	DIMENSIONS
170B-112	60-65 PM	1250-1300Hz	0.5 AMPS	12-24 VDC	128mm (L) 95mm (W) 78mm (H)
170B-94-112	60-65 PM	1250-1300Hz	0.2 - 0.7 AMPS	12-24 VDC	128mm (L) 95mm (W) 78mm (H)
170B-112FA	60-65 PM	1250-1300Hz	0.8 AMPS	12-24 VDC	128mm (L) 95mm (W) 78mm (H)

180B



PART NO.	SOUND CYCLE	FREQUENCY	CURRENT DRAW @12v	OPERATING VOLTAGE	DIMENSIONS
180B-87-112	60-65 PM	1250-1400Hz	0.2 - 0.8 AMPS	12-24 VDC	95mm (L) 175mm (W) 80mm (H)

DESCRIPTION

- 160 Plastic Housing: Nylon Plus 30% Fiber
- 170 and 180 Plastic Housing: Nylon Plus 33% Fiber
- 160 Series with Earthing Strap
- 170 and 180 Series without Earthing Strap
- Operating Temperature: -40 to 80 Degrees Celsius
- IP66 Rated - Splash and Dust Proof