



|  |                           |
|--|---------------------------|
|  | WATER CONNECTION 3/4" GAS |
|  | DRAINING PIPE Ø 24mm      |
|  | ELECTRICAL SUPPLY         |

(\*\*\*) MIN 130-MAX 200 mm

| TECHNICAL DATA             |                                       |        |        |        |        |
|----------------------------|---------------------------------------|--------|--------|--------|--------|
| <b>EXTERNAL DIMENSIONS</b> |                                       |        |        |        |        |
| width                      | 720 mm                                |        |        |        |        |
| depth                      | 735 mm                                |        |        |        |        |
| height                     | 1445/1915(open hood) mm               |        |        |        |        |
| WEIGHT(basic version)      | 104 kg                                |        |        |        |        |
| VOLTAGE                    | 400V 3N 50Hz                          |        |        |        |        |
| POWER REQUIRED             | 10490 W                               |        |        |        |        |
| WATER HARDNESS             | 2-8 °F                                |        |        |        |        |
| INLET WATER PRESSURE       | 200-400 kPa                           |        |        |        |        |
| <b>CROCKERY DIMENSIONS</b> |                                       |        |        |        |        |
| plates diameter            | 410 mm                                |        |        |        |        |
| trays max. dimension       | 600X400 mm                            |        |        |        |        |
| RACK DIMENSION             | 500X500+SPECIAL STEEL RACK 500X600 mm |        |        |        |        |
| RACK EQUIPMENT             | 1XC44 - 1XC86/A - 1X11600054          |        |        |        |        |
| WASHING CYCLES (sec)       | 1 (50)                                | 2 (90) | 3(120) | 4(180) | 5(300) |
| <b>WATER SUPPLY 55°C</b>   |                                       |        |        |        |        |
| racks/h(*) <sup>(1)</sup>  | 72                                    | 40     | 30     | 20     | 12     |
| <b>WATER SUPPLY 10°C</b>   |                                       |        |        |        |        |
| racks/h(*) <sup>(1)</sup>  | 35                                    | 35     | 30     | 20     | 12     |
| WATER CONSUMPTION / CYCLE  | 2.6 l                                 |        |        |        |        |
| BOILER CAPACITY            | 15 l                                  |        |        |        |        |
| BOILER HEATING ELEMENT     | 9000 W                                |        |        |        |        |
| RINSING TEMPERATURE (SET)  | 85°C                                  |        |        |        |        |
| TANK CAPACITY              | 42 l                                  |        |        |        |        |
| TANK HEATING ELEMENT       | 2700 W                                |        |        |        |        |
| TANK TEMPERATURE (SET)     | 55°C                                  |        |        |        |        |
| PUMPS POWER washing        | 1490 W (800 l/min <sup>***</sup> )    |        |        |        |        |
| DRAIN PUMP (optional)      | 25 W (40 l/min <sup>***</sup> )       |        |        |        |        |
| NOISE                      | 61.3±0.7 dB(A)                        |        |        |        |        |

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(†) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.