

PANTHER by ANTONIOCARRARO



Panther 22 M

Panther 26 M

Panther 26 H



MODEL	PANTHER 22 M	PANTHER 26 M	PANTHER 26 H
ENGINE			
Brand	Mitsubishi	Mitsubishi	Mitsubishi
Power supply	Diesel	Diesel	Diesel
Rated power (ECE R120)	16.3 KW / 22 HP	18.2 KW / 25 HP	18.2 KW / 25 HP
Emissions standard	Stage V	Stage V	Stage V
Number of cylinders	3	3	3
Cooling	Liquid	Liquid	Liquid
Displacement	953 cc	1318 cc	1318 cc
Maximum torque	52 Nm@2000rpm	76.3 Nm@2000rpm	76.3 Nm@2000rpm
Tank capacity	20 l	20 l	20 l
TRANSMISSION			
Transmission type	Mechanical, 4WD	Mechanical, 4WD	Hydrostatic, 4WD
Gearbox type	9+3 mechanical	9+3 mechanical	Low - Medium - High
Gearbox control	Mechanical with side levers	Mechanical with side levers	Pedals
Clutch	Single dry	Single dry	-
Rear differential lock	yes	yes	yes
Maximum speed	23km/h	23km/h	23km/h
BRAKES			
Rear braking system	Oil-immersed multi-disc, mechanical control	Oil-immersed multi-disc, mechanical control	Oil-immersed multi-disc, mechanical control
STEERING			
Steering type	Power steering	Power steering	Power steering
POWER TAKE-OFF REAR			
PTO speed	540/540E	540/540E	540/540E
Mid-mounted PTO	-	-	yes
PTO engagement	Mechanical with lever	Mechanical with lever	Mechanical with lever
REA POWER LIFT			
Lifting system type	Hydraulic with manual control, lift-lower and position control	Hydraulic with manual control, lift-lower and position control	Hydraulic with manual control, lift-lower and position control
Draft control	yes	yes	yes
Lifting capacity	750 Kg	850 Kg	900 Kg
Three-point linkage category	Category 1	Category 1	Category 1
Mechanical top link	Category 1	Category 1	Category 1
TOWING DEVICES			
Tow hook	yes	yes	yes
HYDRAULIC SYSTEM			
Type	Open centre	Open centre	Open centre
Pump	No. 1	No. 2 (one for hydrostatic steering and one for hydraulic system)	No. 2 (one for hydrostatic steering and one for hydraulic system)
Capacity	11 l/min	11+11 l/min	11+11 l/min
Rear hydraulic spool valves	1 double-acting	1 double-acting	1 double-acting
ELECTRICAL SYSTEM			
Safety	Battery cut-off switch	Battery cut-off switch	Battery cut-off switch
Work lights	2 front	2 front	2 front
OPERATOR STATION			
Rear-view mirror	No.2	No.2	No.2
Mechanically adjustable seat	With seat belts	With seat belts	With seat belts
ROPS	rear	front	front or rear
SIZE AND WEIGHTS			
Pitch	1490 mm	1490 mm	1550 mm
Total length	2850 mm	2850 mm	2780 mm
Width (min-max)	Front 23X8.5/12 Rear 280/70R18 1220÷1270 mm Front 6.5/80-12 Rear 280/70R18 1200÷1270 mm	Front 23X8.5/12 Rear 280/70R18 1220-1303 mm Front 6.5/80-12 Rear 280/70R18 1200-1303 mm	Front 23X8.5/12 Rear 280/70R18 1220-1270 mm
Kerb weight	900 kg	950 Kg	1035 kg