



ItalianGelato
Concepts
dessert-projects & equipment supply



MICROGEL


MICROGEL



HORIZONTAL COUNTER ICE CREAM AND GASTRONORM SHOWCASE

- Removable condenser filter
- Stainless steel ventilation grids, integrated in the structure
- Predisposed with stainless steel bars for ice cream stainless steel basins
- Electronic control unit with display and integrated control panel
- Feet as standard
- Condenser filter cleaning alarm
- PMMA cover with chromed handles, opening from operator side
- LED lighting with high luminous efficiency and energy savings
- Stainless steel frame with PMMA sides and upper opening cover

MICROGEL 4



Colori standard



COD. 08

	°C	LxDxH mm	N° - mm. DI SERIE	N° - mm. MAX	Watt	% U.R.	DEFROST	H ₂ O			Kg.		
Microgel 2	-15/+18	722x560x467	-	n° 4 - Lt. 2,5 n° 2 - Lt. 5 / Lt. 7	180	-		MAN		R404A	32	-	LED di serie
Microgel 3	-15/+18	897x560x467	-	n° 6 - Lt. 2,5 n° 3 - Lt. 5 / Lt. 7	180	-		MAN		R404A	35	-	LED di serie
Microgel 4	-15/+18	1072x560x467	-	n° 8 - Lt. 2,5 n° 4 - Lt. 5 / Lt. 7	180	-		MAN		R404A	40	-	LED di serie
Microgel 2 GN	+2/+8	722x560x467	-	n° 2 GN 1/3 o n° 4 GN 1/6 h. 100 o 150 mm.	180	-		MAN		R404A	32	-	LED di serie
Microgel 3 GN	+2/+8	897x560x467	-	n° 3 GN 1/3 o n° 6 GN 1/6 h. 100 o 150 mm.	180	-		MAN		R404A	35	-	LED di serie
Microgel 4 GN	+2/+8	1072x560x467	-	n° 4 GN 1/3 o n° 8 GN 1/6 h. 100 o 150 mm.	180	-		MAN		R404A	40	-	LED di serie

Standard voltage: 230v/1/50Hz • Climatic class: MAX = (25°C - % U.R. 60)