

KTH1165-INOX

20 L/min, 2400psi

Hot water up to 150°C

2 YEAR
COMMERCIAL
WARRANTY

Made
in
Germany

HEAVY DUTY
4-POLE MOTOR
1400
RPM



Technical Data

KTH1165-INOX

| | |
|--------------------------------|-------------------|
| Phase: | Three Phase |
| kW: | 5.5 |
| RPM: | 1400 |
| Litre/min: | 20 |
| Operating/max. pressure (psi): | 2400 |
| Total Stop: | Yes + Delay |
| kg: | 223 |
| Hose: | 20m Drum |
| Detergent Injector: | High Pressure |
| Size (mm): | 1050 x 800 x 1015 |

- Three phase
- 7.5m power lead
- Cable reel
- Steel fabric high pressure, 20m with hose drum
- Water tank
- Stainless steel lance with flat jet nozzle
- Total-stop function with delayed motor cut-out
- Continuously adjustable pressure & temperature control
- 4 Way safety system with overload protection
- Optical flame monitoring and integrated steam level
- Pre-aeration of combustion chamber
- 35L fuel tank with content monitoring
- Brass pump head
- Ceramic coated pump plungers
- Dry-run safety and leakage return system
- High pressure detergent application
- Two year industrial warranty.
- **Stainless-Steel heating coil**

Optional Accessories

Hose Reel with 20m Hose

Also includes 1m steel braid high pressure hose for fitting (#44152)



Lance Extension

ST30 x M22 – 1000mm (#41154)



Standard Spray Lance

600mm c/w Knife Jet Nozzle (#123922-D2507)



Turbo Killer Lance - Complete

Lance + Nozzle - 07, 600mm (#410727)



Wire Braided High Pressure Hose

M22, F/F
20m
400bar
NW8
(#41083)



Round Floor Cleaners

300 (#41105)
420 (#41106)
520 (#41107)

