

PRODUCT SPECIFICATIONS FOR 773G



ENGINE

Engine Model	Cat® C27
Rated Engine Speed	2000 r/min
Gross Power - SAE J1995	578 kW
Net Power - SAE J1349	542 kW
Net Power - 80/1269/EEC	542 kW
Net Power - ISO 9249	542 kW
Bore	137 mm
Stroke	152 mm
Displacement	27 l
Engine Power - ISO 14396	607 kW
Net Torque	3896 N·m
Note (3)	No engine derating required up to 3810 m (12,500 ft) for Tier 2 Equivalent.
Peak Torque - Speed	1300 r/min
Note (2)	Ratings based on SAE J1995 standard air conditions of 25° C (77° F) and 100 kPa (29.61 Hg) barometer. Power based on fuel having API gravity of 35 at 16° C (60° F) and an LHV of 42 780 kJ/kg (18,390 BTU/lb) when engine used at 30° C (86° F).

Note (1)

Power rating applies at 2,000 rpm when tested under the specified condition for the specified standard.

WEIGHTS - APPROXIMATE

Maximum Gross Vehicle Weight

102740 kg

OPERATING SPECIFICATIONS

**Nominal Payload Class
(100%)**

56 t

Top Speed - Loaded

67.6 km/h

**Maximum Working Payload
(110%)**

61.5 t

Body Capacity - SAE 2:135.75 m³**Note (2)**

* Refer to the Caterpillar 10/10/20 Payload Policy for maximum gross machine weight limitations.

Note (1)

Capacity with Dual Slope body – no liner.

**Maximum Allowable Payload
(120%)***

67.1 t

Target Payload (100%)

56 t

TRANSMISSION

Forward - 1

10.8 km/h

Forward - 2

15.1 km/h

Forward - 3

20.4 km/h

Forward - 4

27.4 km/h

Forward - 5

37 km/h

Forward - 6	50.1 km/h
--------------------	-----------

Forward - 7	67.6 km/h
--------------------	-----------

Reverse	14.1 km/h
----------------	-----------

Note	Maximum travel speeds with standard 24.00R35 (E4) tires.
-------------	--

FINAL DRIVES

Differential Ratio	3.64:1
---------------------------	--------

Planetary Ratio	4.80:1
------------------------	--------

Total Reduction Ratio	17.49:1
------------------------------	---------

BRAKES

Brake Surface - Front	655 cm ²
------------------------------	---------------------

Brake Surface - Rear	61269 cm ²
-----------------------------	-----------------------

Brake Standards	ISO 3450:2011
------------------------	---------------

BODY HOISTS

Pump Flow - High Idle	448 l/min
------------------------------	-----------

Relief Valve Setting - Raise	17250 kPa
-------------------------------------	-----------

Relief Valve Setting - Lower	3450 kPa
-------------------------------------	----------

Body Raise Time - High Idle	9.5 s
------------------------------------	-------

Body Lower Time - Float	13 s
--------------------------------	------

Body Power Down - High Idle	13 s
------------------------------------	------

CAPACITY - DUAL SLOPE - 100% FILL FACTOR

Struck 26.86 m³

Heaped (SAE 2:1)* 35.75 m³

Note (1) Contact your local Cat dealer for body recommendation.

Note (2) * ISO 6483:1980.

CAPACITY - FLAT FLOOR - 100% FILL FACTOR

Struck 26.25 m³

Heaped (SAE 2:1)* 35.49 m³

Note (1) Contact your local Cat dealer for body recommendation.

Note (2) * ISO 6483:1980.

WEIGHT DISTRIBUTIONS - APPROXIMATE

Front Axle - Empty 53 %

Front Axle - Loaded 35 %

Rear Axle - Empty 47 %

Rear Axle - Loaded 65 %

SUSPENSION

Rear axle - Oscillation 8.1 °

Empty Loaded Cylinder Stroke Rear 149 mm

Empty Loaded Cylinder Stroke Front 234 mm

SERVICE REFILL CAPACITIES

Fuel Tank 795 l

Cooling System	171 l
Differential - Final Drives	145 l
Steering Tank	36 l
Steering System - Including Tank	54 l
Crankcase	90 l
Torque Converter - Transmission System - LRC	61 l
Brake Hoist System	322 l
Brake/Hoist Hydraulic Tank	176 l

TIRES

Note (2)	Caterpillar recommends the customer evaluate all job conditions and consult the tire manufacturer for proper tire selection.
Note (1)	Productive capabilities of the 773G truck are such that, under certain job conditions, TKPH (TMPH) capabilities of standard or optional tires could be exceeded and, therefore, limit production.
Standard Tire	24.00R35 (E4)

ROPS

ROPS Standards	Rollover Protective Structure (ROPS) for cab offered by Caterpillar meets ISO 3471:2008 ROPS criteria.
FOPS Standards	Falling Object Protective Structure (FOPS) meets ISO 3449:2005 Level II FOPS criteria.

SOUND

Sound Standards (2)	The exterior sound pressure level for the standard machine measured at a distance of 15 m (49 ft) according to the test procedures specified in SAE J88:2008, mid-gear moving operation is 86 dB(A).
----------------------------	--

Sound Standards (3) Hearing protection may be needed when operating with an open operator station and cab (when not properly maintained or doors/windows open) for extended periods or in a noisy environment.

Sound Standards (1) The operator Equivalent Sound Pressure Level (Leq) is 76 dB(A) when SAE J1166 FEB2008 is used to measure the value for an enclosed cab. This is a work cycle sound exposure level. The cab was properly installed and maintained. The test was conducted with the cab doors and the cab windows closed.

STEERING

Turning Diameter - Front 23.5 m

Steering Standards SAE J1511 FEB94 ISO 5010:1992

Steer Angle 31 °

Turning Circle - Clearance Diameter 26.1 m

773G STANDARD EQUIPMENT

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

POWER TRAIN

Cat C27 Tier 4/Stage V compliant diesel engine:

- Air cleaner with precleaner (2)
- Air-To-Air Aftercooler (ATAAC)
- Electric start
- Engine idle shutdown
- Ether starting aid
- Exhaust muffler
- NGMR radiator

For non-regulated regions only:

- Direct drive fan
- MEUI-A fuel system

Braking system:

- Extended Life Brakes
- Automatic Retarder Control (ARC)
- Manual retarder (utilizes rear oil-cooled, multiple disc brakes)
- Brake release motor (towing)
- Dry disc brakes (front)
- Front brake disconnect switch (front)
- Oil-cooled multiple disc brakes (rear)
- Brake wear indicator (rear)
- Parking brake
- Secondary brake
- Service brake

Transmission:

- 7-speed automatic powershift with:
Electronic Clutch Pressure Control (ECPC)
Advanced Productivity Electronic Control Strategy (APECS)
- Automatic neutral idle
- Autostall
- Second gear start

SUSPENSION SYSTEMS

Suspension, front and rear (EU compliant)

ELECTRICAL

Alarm backup

Alternator, 120 Amp

Autolube power supply ready

Batteries, maintenance-free, 12V (2), 1,400 CCA combined

Electrical system, 25 Amp, 24V to 12V converter

Lighting system:

- Backup light (halogen)
- Directional signals/hazard warning (front and rear LED)
- Engine compartment light
- Headlights, (halogen) with dimmer
- Operator access courtesy lights
- Side profile lights
- Stop/tail lights (LED)

Service center containing:

- Battery jump start
- Breakers with spare fuses
- Lockout switch
- Ports, ET and VIMS
- Service lockout switch (power without engine start)

TECHNOLOGY PRODUCTS

Economy Modes, standard and adaptive

Product Link, cellular or satellite
Traction Control System (TCS)
Truck Production Management System
Vital Information Management System (VIMS)

OPERATOR ENVIRONMENT

Advisor display:

- Air cleaner service indicator
- Fluid level monitoring
- Fuel level monitoring
- Display languages (market-based)

Air conditioning/heat

Automatic temperature control

Ashtray and cigarette lighter

Coat hook

Cup holders (4)

Diagnostic connection port, 24V

Entertainment radio ready:

- 5 amp converter
- Speakers
- Antenna
- Wiring harness

Foot rest

Gauges/indicators:

- Brake oil temperature gauge
- Coolant temperature gauge
- Engine overspeed indicator
- Fuel level
- Hour meter
- Speedometer with odometer
- Tachometer
- Transmission gear indicator

Hoist lever

Horn

Light - courtesy

Light - dome

Mirrors, non-heated

Power port, 24V and 12V (2)

Rollover Protection (ROPS)/Falling Object Protection (FOPS)

Seat, Cat Comfort Series III:

- Full air suspension
- Retractable 3-point seat belt with shoulder harness

Seat, training with lap belt

Steering wheel, padded, tilt and telescopic

Storage compartment

Sun visor

Throttle lock

Window, hinged, right side (emergency exit)

Window, powered, left side
Windshield wiper intermittent and washer

GUARDS

Driveline
Engine crankcase
Fan

FLUIDS

Antifreeze
Extended life coolant to -34° C (-30° F)
Grouped ground-level filters

OTHER STANDARD EQUIPMENT

Body down indicator
Body safety pin (secures body in up position)
Center-mounted rims
Fuel tank, 795 L (210 gal)
Ground level battery disconnect
Ground level engine shutdown
Ground level grease fittings
Operator Maintenance Manual (OMM)
Rims 17 × 35
Rock ejectors
Secondary steering (electric)
Tie down eyes
Tow hooks (front)/tow pin (rear)
Vandalism protection locks

773G OPTIONAL EQUIPMENT

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

OPTIONAL EQUIPMENT

Body heat
Body liner
Body sideboards
Cab precleaner
Cat Engine Brake
Clustered grease fittings
Cold weather packages
Fluid fill service center
HID lights
Mirrors, convex

Mirrors, heated

Spare rim

Visibility package (meets ISO 5006 requirements)

Wheel chocks

Work Area Vision System (WAVS)