

# Pizza — TP4 SP TN EP

## Catering



### Technical data

---

|                     |                       |
|---------------------|-----------------------|
| Gross volume        | 609 lt                |
| Working temperature | 0+8 °C                |
| Motor type          | Remote                |
| Refrigerant         | R452A                 |
| Refrigeration power | 482 W (-10°C / +45°C) |
| Absorption          | 204 W                 |
| Voltage/Frequency   | 230V/1~/50Hz          |

### Refrigeration details

---

|                        |   |
|------------------------|---|
| Refrigeration unit     | Remote with possibility to get as optional protection cover |
| Evaporator             | With cataphoresis anti-corrosion treatment                  |
| Defrost                | Automatic by air  |
| Condensate evaporation | Automatic by electric heater                                |

## Construction details

---

|                            |   |
|----------------------------|---|
| Product dimensions WxDxH   | 2500x800x860  |
| Packaging dimensions WxDxH | 2550x850x1000   |
| Gross weight               | 177 Kg  |
| Worktop                    | Without worktop   |
| Structure                  | Stainless steel AISI 304 monocoque  |
| External/Internal material | Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel |
| Insulation thickness       | 60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)                      |
| Inner corners              | Rounded for an easy cleaning  |
| Door                       | 4 Self-closing doors with 105° door stop, reversibles on site   |
| Door gasket                | Magnetic and removable, designed to improve insulation and to reduce energy consumption   |
| Feet                       | AISI 304 stainless steel, height adjustable (135mm-230mm)   |

## Functions

---

|               |  |
|---------------|--|
| Control panel | Compact, simple and intuitive touch screen display. Tilted control panel |
|---------------|--|

## Accessories

---

|                          |   |
|--------------------------|---|
| No. included accessories | 4 - Plastic-coated grid EN 600x400 mm<br>4 - Pair of runners for grid EN 600x400 mm |
|--------------------------|---|

## Remote unit data

---

|                                       |                  |
|---------------------------------------|------------------|
| Refrigerant gas for remote motor unit | Set up for R452A |
|---------------------------------------|------------------|

## Versions

---

|          |                             |
|----------|-----------------------------|
| Versions | Power supply frequency 60Hz |
|----------|-----------------------------|