



Talent – TA 6V TA 6V BK

Ice-cream 6 x 5lt Tray Capacity



Technical data

Gross volume	159 lt
Working temperature	-40+10 °C
Performance from +90°C to +3°C	21 Kg
Performance from +90°C to -18°C	15 Kg
Motor type	Plug-in
Refrigerant	R452A
Refrigeration power	1748 W (-10°C / +40°C)
Absorption	1180 W
Voltage/Frequency	230V/1~/50Hz

Refrigeration details

Refrigeration unit	Tropicalized condensing unit. Equipped with thermostatic valve. Condenser is oversized to ensure maximum efficiency and performance
Refrigerant charge	900 gr
Evaporator	Conceived to provide the maximum exchange surface and to ensure optimal performance. Equipped with cataphoresis anti-corrosion treat- ment and door that can be opened for an easy cleaning
Defrost	Manual by air. The equipment can work for 24 hours avoiding ice for- mation on the evaporator
Condensate evaporation	Through easy extractable condensation collector tray (for installations without water drain system)





Italian Gelato Concepts Pty Limited Unit 1, 37 Mortimer Road Acacia Ridge Qld 4110 Bris +61 (0) 7 3162 7724 : Syd +61 (0) 2 8311 9701 info@italiangelato.com.au : www.italiangelato.com.au





Construction details

Product dimensions WxDxH 800x750x840 Packaging dimensions WxDxH 870x840x980 Gross weight 116 Kg Worktop Sturdy and resistant stainless steel AISI 304 worktop with rounded edges Structure Stainless steel AISI 304 monocoque conceived with an innovative and functional design
Gross weight 116 Kg Worktop Sturdy and resistant stainless steel AISI 304 worktop with rounded edges Structure Stainless steel AISI 304 monocoque conceived with an innovative and
Worktop Sturdy and resistant stainless steel AISI 304 worktop with rounded edges Structure Stainless steel AISI 304 monocoque conceived with an innovative and
edges Structure Stainless steel AISI 304 monocoque conceived with an innovative and
External/Internal material Inside and outside in stainless steel AISI 304; motor unit compartment and bottom in colaminated steel
Insulation thickness60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Door 1 Self-closing door right hinged, not reversible on site
Door gasket Magnetic and removable, designed to improve insulation and to re-
duce energy consumption

Functions

Control panel	7" touch screen graphic display
Open door alarm	Visual and acoustic
Functions	Soft and hard blast chilling, soft and hard blast freezing, slow cooking, retarder proving, thawing, holding, automatic end cycle holding, multi- level continuous cycle, special cycles: ice-cream hardening, ice-cream tempering, chocolate crystallization, yoghurt, high and low pasteuriza- tion, dessication, preloaded recipes, 100 customizable recipes, HACCP alarms
Languages	Italian, English, French, German, Spanish, Portuguese, Russian
Probe	Needle probe with precision finish to facilitate extraction from the fro- zen product. Temperature detection through 3 sensors and automatic recognition of the probe inserted in the food
Connection	As optional: Remote access through serial interface. Via APP (only Android) it is possible to monitor HACCP traceability, appliance opera- tion and parameters. Graphic and as CVS file export of registered data. Email sending of alarms notification

Accessories

No. included accessories

2 - Stainless steel grid EN 600x400 mm2 - Pair of runners for GN 1/1 and EN 600x400 mm

Versions

Versions

Water cooling unit/ Power supply frequency 60Hz

Technical datasheet EN Talent 6V & 6V BK Ice-cream

Updated on 06-04-2022



Italian Gelato Concepts Pty Limited Unit 1, 37 Mortimer Road Acacia Ridge Qld 4110 Bris +61 (0) 7 3162 7724 : Syd +61 (0) 2 8311 9701 info@italiangelato.com.au : www.italiangelato.com.au