

XL Hood Type Dishwasher

AH60.42EPRS

Product Information:

- High performance XL hood-type dishwasher
- E-Management: intuitive and advanced electronic interface
- PRS System: break tank, 316 atmospheric boiler, rinse booster pump
- HD System: for maximum uninterrupted performance
- Increased capacity with 600x500mm baskets (500x500mm compatible)
- XL Filters robust and additional upper tank scrap filters in stainless steel
- Larger HP vertical self-draining wash pump
- Larger HI FLOW stainless steel wash and rinse arms
- Larger elements in wash tank and boiler
- Four wash cycles 90/120/180 seconds, and 9 minute deep clean
- Green standby function that reduces energy consumption when idle
- Low water consumption of 2.5 litres per cycle, minimising water, energy and detergent use
- Pressed wash tank with rounded corners, for increased hygiene
- Manual lift with fully enclosed rear, 3 spring support
- Automatic drain pump with self-cleaning function
- Built in thermostop, ensures correct rinse temperatures
- Built in detergent and rinse-aid injection
- 18-months parts and labour warranty

Included Accessories:

- 1 x glass rack 500x600mm
- 2 x plate rack 500x600mm
- 2 x cutlery basket
- 1 x water inlet hose (length 1.5m)
- 1 x drain hose (length 2m)
- Fitted with 150mm adjustable legs

Optional Accessories:

- Twin hood system
- Remote interface
- Inlet and outlet benches
- Additional baskets



992

589

793

Specifications:

Model AH60.42EPRS $W \times D \times H (mm)$ 681 x 793 x 2016* Note: Dimensions do not include handle. Hood open

Weight 141kg

Packed Dimensions (mm) 770 x 930 x 1720

Packed Weight 160kg

Total Connected Load 14.8kW

- Convertible to: 10.3kW (low power option)

Note: Unit can be converted to low power option on site by a

Electrical Connection 3Ø+N+E 415VAC / 50Hz

(Lead fitted, onsite connection)

Water Quantity Per Cycle 2.5 Litres

1.5m Hose / 3/4" BSP **Water Connection** 100 - 500KPA Water Inlet Pressure

Tempered water supply 10°C - 60°C

Waste Connection 2m Hose / ø20.5mm

Legend:

C

Δ **Flectrical Connection** В Water Connection

Drain Connection D **Detergent Connection**

Ε Rinse-Aid Connection

0

207

O

O



498

681

785

(1494 min - 1589 max

537

1969 min - 2064 max)

2016 (

(max drain

8

<u>| | 180 | 88</u>

www.stoddart.com.au www.stoddart.co.nz

