

SOLOSCAN

Fixed Transducer Solution



Specifications

Net weight	Approx 170g
Size	150mm x 40mm x 25mm
Battery life	Approx 4 hours
Application Platforms	Android, Windows, iOS
Connection type	WiFi + USB
Supported devices	Smart Phone, Tablet or PC
Modes	B, BM, 2B, THI, Power, PW, Colour
Voice Control	15+ Commands (iOS / Android)
Language	Multiple Languages Supported
Function Control	Buttons on Device, Touchscreen + Voice Controls
DICOM	Patient information management DICOM 3.0
Image Storage	Local, DICOM, email
Reporting	Customisable Templates
Charging	Magnetic or USB-C
Waterproof Rating	IPX6



4hr Battery Life



No Membership



Android / iOS + Windows

Fixed Transducer				
Transducer	Code	Frequency (MHz)	Depth (cm)	Footprint (cm)
Small Linear	P50F-L11-4Gs	6-11	14	2.5
Large Linear	P50F-L11-4Ks	6-11	14	4
High Frequency Linear	P50F-L12-4Ks	6-12	14	4
Small Convex	P50F-C8-5Ks	5-8	14	1.5
Medium Convex	P50F-C5-2Fs	2-5	30	5
Large Convex	P50F-C5-2Ks	2-5.5	30	6
Transvaginal	P50F-E10-4Ks	5-8.5	14	1

2 year warranty / Extended warranty available / No membership required