

10 TROLLEY HIGH-CAPACITY INDUSTRIAL DEHYDRATOR

INDUSTRIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL




Save Set Recipes



CSV Data Export



Completion Cooling Cycle



Uniform Drying Without Rotation



Programmable Staged Drying



DrySync™ Technology



Remote Operational Control



Food-Grade 304 Stainless Steel

MODEL IU10 SPECIFICATIONS

Max Power Rating	54 kW	Internal Airflow	27200 m ³ /hr
Avg. Power Rating	28-30 kW	Number of Exhaust Fans	5
Voltage / Frequency	3-Phase / 50-60Hz - 400V, Custom	Total Trolleys	10 Trolley
Product Dimension (W x H x D)	2500 x 2200 x 5200 mm	Trolley Dimensions	920 x 1450 x 695 mm
Loading Footprint Required	2500 x 2200 x 6600 mm	Space Between Trays	40 - 80 mm
Machine Weight	3100 kg	Total Trays	300 - 600 trays
Temperature Range	Ambient - 150°C or 300°C Upon Request	Tray Dimensions	460 x 640 mm
Exhaust Air Volume	850 m ³ /hr (per Exhaust Fan)	Total Tray Area	88.3 - 176.6 m ²
Static Pressure Rating	1020 pa (per Exhaust Fan)	Timer	0 - 5000 hours
Product Material	Double walled industrial-grade 304 stainless steel. Insulated with high density aluminium silicate cotton.		