

**FOR CNC MACHINE**

**AJAX -02**

# OIL WATER SEPARATOR

- ✓ Automatic control
- ✓ Accurate positioning
- ✓ Easy to move
- ✓ Ozone sterilizaton
- ✓ One for multiple machines



**CNC**  
MACHINERY SALES AUSTRALIA

**FOR CNC MACHINE**

**AJAX -02**

# OIL WATER SEPARATOR

Effectively solve the deterioration of the cutting fluid and smell !

No worry about the interference of iron filings, regular cleaning and no consumption!

Extend the service life of cutting fluid and reduce production costs !

Ozone sterilization, purifies the cutting fluid while sterilizing and deodorizing !



**PRODUCT DETAILS >>**

## FOR CNC MACHINE OIL WATER SEPARATOR



# FOR CNC MACHINE OIL WATER SEPARATOR

## TECHNICAL SPECIFICATIONS >>

Input Voltage	AC 110/220V 50/60Hz
Input Power	30W
Pump Motor Speed	0-90rpm Step-less Adjustable
Timing Range	0-99h Circulation
Oil Tank Capacity	9L
Ozone output	1000mg/h
Operating Temperature	0°C--45°C
Filter Bottle Size	10 inches
Filter Hole Size	3mm
Inlet Pipe Inner Diameter	16mm
Outlet Pipe Inner Diameter	25mm
Drainage Pipe Inner Diameter	19mm
Overall Dimensions ( L*W*H)	600*350*580mm
Net Weight	33.2Kg

Before separating



After separating



**CNC**  
MACHINERY SALES AUSTRALIA